

ARAMID PACKING N1706

Composition

Speciale inorganic fibres
Impregnated with PTFE and solid lubricant

Characteristics

The aramid packing N1706 DINACOMB is braided with special organic fibres harder taht the aramid. These yarns ensure great chemical resistance and very low coefficient of friction for long time. Each yarn is impregnated with PTFE dispersion and solid lubricant. The pump packing N1706 DINACOMB is the right packing for dynamic applications where is working a classic aramid packing.

Applications

Pump Packing

Tech Data

	P bar	lbf/in2	Vm/S	f/pm	рН	т°С	T°F
F	500	7500	3	600	1 ÷ 13	÷ 260	÷ 500
®	25	375	15	3000	1 - 13		

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures



Aramid Packing N1706

Special pump compression packing made with high tenacity organic fibres coming form aramid, specific for dynamic applications with abrasive fluids





ARAMID PACKING N1706

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8"	1	2.2	100.0	328.1	100.0	149.0
4	-	1	2.2	47.6	156.2	47.6	70.9
5	3/16"	1	2.2	30.3	99.4	30.3	45.1
6	-	2.5	5.5	55.6	182.4	22.2	33.1
6.5	1/4"	2.5	5.5	50.0	164.0	20.0	29.8
8	5/16"	2.5	5.5	32.5	106.6	13.0	19.4
9.5	3/8"	2.5	5.5	22.7	74.5	9.1	13.5
10	-	2.5	5.5	20.8	68.2	8.3	12.4
11	7/16"	2.5	5.5	15.9	52.2	6.4	9.5
12	-	2.5	5.5	14.7	48.2	5.9	8.8
12.7	1/2"	2.5	5.5	13.2	43.3	5.3	7.9
14	9/16"	5	11	20.8	68.2	4.2	6.2
16	5/8"	5	11	16.1	52.8	3.2	4.8
17.5	-	5	11	13.3	43.6	2.7	4.0
18	11/16"	5	11	11.9	39.0	2.4	3.5
19	3/4"	5	11	11.5	37.7	2.3	3.4
22	7/8"	5	11	8.6	28.2	1.7	2.6
25.5	1"	5	11	6.7	22.0	1.3	2.0



The weight per meter and the packaging's weight may have a tolerance of +/- 10%. Other sizes and packaging are available on demand.



