



EXPANDED GRAPHITE PACKING GR80SGR

Composition

Expanded mineral graphite
Special reinforcement nickel-alloy
Impregnation with graphite-based compound and special components

Characteristics

GR80SGR is composed by expanded graphite strands with a special reinforcement that increases its strength and durability. This expanded graphite packing offers superior performance at high temperatures and very low weight loss during operation, ensuring reliable sealing over time. GR80SGR complies with EN14772 - section 6.7 requirements, ensuring maximum safety in high-pressure applications. With its low coefficient of friction, this expanded graphite packing ensures effective sealing even in extreme conditions. In addition, the Low Emission ISO 15848 certification makes GR80SGR the ideal solution for applications that require low environmental impact and high energy efficiency. With its reliability and ability to maintain elastic and sealing properties over time, GR80SGR minimizes the need for maintenance and saves long-term time and costs.

Applications

The GR80SGR packing is specially designed for low emission industrial valves and those operating under high pressure and temperature conditions. Thanks to its excellent sealing properties, this expanded graphite packing represents the ideal choice for applications that require a high level of reliability and safety, ensuring resistance to reciprocal dynamic stresses, such as those typical of valve opening and closing services. This expanded graphite packing offers maximum flexibility of use, adapting to different application needs and ensuring high performance even in extreme conditions.

Tech Data

| | P bar | lbf/in2 | Vm/S | f/pm | pH | T°C | T°F |
|--|-------|---------|------|------|--------|------------------|-------------------|
| | 500 | 7500 | 1 | 200 | 0 ÷ 14 | -200 ÷ 450 / 650 | -330 ÷ 840 / 1200 |
| | 100 | 1500 | 1 | 200 | | | |

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 ° C
- With steam and non-oxidizing fluids the temperature must be limited to 650 ° C
- Graphite and carbon cannot be used with oxidizing fluids



Expanded Graphite Packing GR80SGR

The Carrara graphite gland packing product range includes items made with all available graphite yarns, which, according to ASTM F2191 classification, are Type I—Continuous yarn, Type II—Staple yarn, and Type III—Flexible yarn. All graphite gland packings are protected with passive or active corrosion inhibitors (Grade A—Treated with corrosion inhibitor), although untreated gland packings (Grade B—No corrosion inhibitor) are available on demand. The performer and premium grade product ranges include Class 2 items, while the Industrial grade product range offers Class 1 products. Carrara graphite gland packings are specialized for each application, and a proper selection of the item allows for maximizing the sealing performance while reducing the component management costs.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

 **CARRARA**
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it



EXPANDED GRAPHITE PACKING GR80SGR

| sezione mm | sezione inch | kg/box | lbs/box | mt/box | ft/box | mt/kg | ft/lbs |
|------------|--------------|--------|---------|--------|--------|-------|--------|
| 3 | 1/8" | 1 | 2.2 | 50.0 | 164.0 | 50.0 | 74.5 |
| 4 | - | 1 | 2.2 | 38.5 | 126.3 | 38.5 | 57.3 |
| 5 | 3/16" | 1 | 2.2 | 22.7 | 74.5 | 22.7 | 33.8 |
| 6 | - | 2.5 | 5.5 | 41.7 | 136.8 | 16.7 | 24.8 |
| 6.5 | 1/4" | 2.5 | 5.5 | 40.3 | 132.2 | 16.1 | 24.0 |
| 8 | 5/16" | 2.5 | 5.5 | 26.3 | 86.3 | 10.5 | 15.7 |
| 9.5 | 3/8" | 2.5 | 5.5 | 21.2 | 69.6 | 8.5 | 12.6 |
| 10 | - | 2.5 | 5.5 | 16.1 | 52.8 | 6.5 | 9.6 |
| 11 | 7/16" | 2.5 | 5.5 | 15.9 | 52.2 | 6.4 | 9.5 |
| 12 | - | 2.5 | 5.5 | 11.9 | 39.0 | 4.8 | 7.1 |
| 12.7 | 1/2" | 2.5 | 5.5 | 11.4 | 37.4 | 4.5 | 6.8 |
| 14 | 9/16" | 5 | 11 | 19.6 | 64.3 | 3.9 | 5.8 |
| 16 | 5/8" | 5 | 11 | 14.3 | 46.9 | 2.9 | 4.3 |
| 17.5 | - | 5 | 11 | 13.3 | 43.6 | 2.7 | 4.0 |
| 18 | 11/16" | 5 | 11 | 11.8 | 38.7 | 2.4 | 3.5 |
| 19 | 3/4" | 5 | 11 | 10.7 | 35.1 | 2.1 | 3.2 |
| 22 | 7/8" | 5 | 11 | 7.8 | 25.6 | 1.6 | 2.3 |
| 25.5 | 1" | 5 | 11 | 6.2 | 20.3 | 1.2 | 1.8 |

- The weight per meter and the packaging's weight may have a tolerance of +/- 10%. Other sizes and packaging are available on demand.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

CARRARA
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it