



# GRAPHITE PACKING GR8048A

## Composition

Flexible expanded graphite strands braided together PAN carbon yarns  
Impregnated with graphite powder and inhibitor of corrosion

## Characteristics

The GR8048A packing is the ideal solution to ensure maximum sealing of industrial valves and pumps, thanks to the combination of carbon fiber and expanded mineral graphite yarns. The special solution based on pure graphite powder and corrosion inhibitor applied to the packing minimizes fugitive emissions, increasing the sealing level. The GR8048A packing is highly elastic and reliable at high temperatures, and thanks to the graphite yarn with continuous PAN carbon fibers, it offers great resistance against extrusion and wear. Easy to install in the stuffing box, GR8048A packing is the ideal solution for multiple industrial applications.

## Applications

The graphite packing GR8048A is equipped with a double yarn, making it particularly versatile and suitable for various industrial applications. Thanks to its high elasticity and reliability at high temperatures, it can be used in high-pressure and high-temperature static services, such as in sealing valves and pumps in chemical and energy processes. Moreover, thanks to its resistance to extrusion and wear, it can be successfully applied in dynamic services, such as those of soot blowers and diathermic oil systems. The graphite packing GR8048A can be used with all non-oxidizing fluids compatible with graphite, ensuring a high level of sealing and minimizing fugitive emissions. The graphite packing GR8048A represents the ideal solution for those seeking a versatile, reliable, and resistant product to use in various industrial applications, ensuring high performance in every operational context.

## Tech Data

	P bar	lbf/in2	Vm/S	f/pm	pH	T°C	T°F
	300	4500	1	200	0 ÷ 14	-100 ÷ 450 / 650	-150 ÷ 840 / 1200
	20	300	2	400			
	40	600	25	5000			

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 ° C
- With steam and non-oxidizing fluids the temperature must be limited to 650 ° C
- Graphite and carbon cannot be used with oxidizing fluids



## Graphite Packing GR8048A

The Carrara graphite gland packing product range includes items made with all available graphite yarns, which, according to ASTM F2191 classification, are Type I—Continuous yarn, Type II—Staple yarn, and Type III—Flexible yarn. All graphite gland packings are protected with passive or active corrosion inhibitors (Grade A—Treated with corrosion inhibitor), although untreated gland packings (Grade B—No corrosion inhibitor) are available on demand. The performer and premium grade product ranges include Class 2 items, while the Industrial grade product range offers Class 1 products. Carrara graphite gland packings are specialized for each application, and a proper selection of the item allows for maximizing the sealing performance while reducing the component management costs.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

 **CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)



# GRAPHITE PACKING GR8048A

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8	1	2.2	85.5	280	85.5	127.3
4	-	1	2.2	48.1	158	48.1	71.6
5	3/16	1	2.2	30.8	101	30.8	45.8
6	-	2.5	5.5	53.4	175	21.4	31.8
6.5	1/4	2.5	5.5	45.5	149	18.2	27.1
8	5/16	2.5	5.5	30	99	12	17.9
9.5	3/8	2.5	5.5	21.3	70	8.5	12.7
10	-	2.5	5.5	19.2	63	7.7	11.5
11	7/16	2.5	5.5	15.9	52	6.4	9.5
12	-	2.5	5.5	13.4	44	5.3	8
12.7	1/2	2.5	5.5	11.9	39	4.8	7.1
14	9/16	5	11	19.6	64	3.9	5.8
16	5/8	5	11	15	49	3	4.5
17.5	11/16	5	11	12.6	41	2.5	3.7
18	-	5	11	11.9	39	2.4	3.5
19	3/4	5	11	10.7	35	2.1	3.2
22	7/8	5	11	7.9	26	1.6	2.4
25.5	1	5	11	5.9	19	1.2	1.8

- The weight per meter and the packaging's weight may have a tolerance of +/- 10%. Other sizes and packaging are available on demand.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

**CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)