

# PTFE JOINTING SHEET PLANIFLON™ B14

## Composition

- Resin of modified PTFE
- Hollow Glass microspheres as filler

#### Characteristics

Planiflon™ B14 is a superior performance biaxially orientated PTFE sheet sealing material with glass spheres filler, very highly conformable properties, ideally suited to both standard and irregular flanges. Planiflon™ B14 has a very low gas permeability, improved creep properties when compared with conventional PTFE gasketing, excellent for handling and cutting. Is specifically designed for use in low bolt loaded irregular flanges. Typical flanges include glass lined, ceramic plastic coated or uneven/badly distorted flanges. It is suitable for sealing all chemicals across the whole pH range, except molten alkali metals, fluorine or hydrogen fluoride.

### **Applications**

Planiflon™ B14 is suitable for applications in a wide range of chemically aggressive fluids. Due to its high compressibility, it is especially recommended for use on flanges and delicate equipment. Planiflon™ B14 is suitable for industrial applications for sealing the flanges and has the following: certificates:

- TA LUFT
- DVGW

#### Tech Data

Planiflon™ B14				
Colour			Blue	
Filler			Hollow glass microspheres	
Density		g/cm³	1.4	
Temperature		°C	-200/+260	
Max operating pressure		bar	50	
P x T max		bar x °C	-	
thickness 0,5 to 2,0			12000	
thickness 3,0			8500	
Compression	DIN 3535-6	%	>32	
Creep	DIN 3535-6	%	<19	
Recovery	DIN 3535-6	%	>7	
Leakage	DIN 3535-6	mg*s-1*m-1	<0.05	
PH Range			0 ÷ 14	

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information The peak temperature can be sustained for short exposures
- Other gasketing sheet dimensions and thicknesses are available on request
- The dimensional tolerances of the gasketing sheets are: W and L  $\pm$  3,0%, H  $\pm$  10,0%

Size	1.500 x 1.500 - (1000 x 1000 sp. 0.75 mm)	60" x 60" - (40" x 40" tk. 1/32")
Thickness	0,75 ÷ 6,00 mm	1/32" ÷ 1/4"



# PTFE Jointing Sheet Planiflon™ B14

The bidirectional structured PTFE gasketing sheets Planiflon™ are made with special resins and inorganic fillers. The special processing technique minimizes the material's cold flow, giving to the sheets the characteristic attribute of bidirectionality. The product range of the Planiflon™ includes the following products:

- B13 Modified PTFE with silica filler
- **B14** Modified PTFE with hollow glass microspheres filler
- B15 Modified PTFE with barium sulphate filler
- B58 Microcellular Modified PTFE layers with pure modified PTFE core
- **B60** Microcellular Modified PTFE with Inorganic fillers
- E12 Bi-directional expanded PTFF



