



RAMIE PACKING R4804

Composition

The pump packing R4804 is made from 100% Ramie yarns impregnated with PTFE and silicone-free lubricant. This braided packing, softer and more elastic than the aramid packings, offers equally good sealing performance while preserving the integrity of the shafts and bearings. R4804 is specific for water services but can work with industrial oil, greases and lubricant.

Characteristics



Ramie yarns
Dispersion of PTFE
Lubricant silicon free

Applications

Packing for pumps and mixers, suggested for marine applications.



Tech Data

	P bar	lbf/in2	Vm/S	f/pm	pH	T°C	T°F
	60	900	2	400	4 ÷ 10	-50 ÷ 120	-60 ÷ 250
	25	375	10	2000			

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures

Ramie Packing R4804

The pump packing R4804 is made from 100% Ramie yarns impregnated with PTFE and silicone-free lubricant. This braided packing, softer and more elastic than the aramid packings, offers equally good sealing performance while preserving the integrity of the shafts and bearings.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

 **CARRARA**
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it



RAMIE PACKING R4804

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8	1	2.2	79.4	260	79.4	118.2
4	-	1	2.2	44.6	146	44.6	66.5
5	3/16	1	2.2	28.6	94	28.6	42.6
6	-	2.5	5.5	49.6	163	19.8	29.6
6.5	1/4	2.5	5.5	42.3	139	16.9	25.2
8	5/16	2.5	5.5	27.9	92	11.2	16.6
9.5	3/8	2.5	5.5	19.8	65	7.9	11.8
10	-	2.5	5.5	17.9	59	7.1	10.6
11	7/16	2.5	5.5	14.8	48	5.9	8.8
12	-	2.5	5.5	12.4	41	5	7.4
12.7	1/2	2.5	5.5	11.1	36	4.4	6.6
14	9/16	5	11	18.2	60	3.6	5.4
16	5/8	5	11	14	46	2.8	4.2
17.5	11/16	5	11	11.7	38	2.3	3.5
18	-	5	11	11	36	2.2	3.3
19	3/4	5	11	9.9	32	2	2.9
22	7/8	5	11	7.4	24	1.5	2.2
25.5	1	5	11	5.5	18	1.1	1.6

- The weight per meter and the packaging's weight may have a tolerance of +/- 10%. Other sizes and packaging are available on demand.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

CARRARA
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it