



PLANIX™ PX03 65SH

Composition

The EPDM (Ethylene-Propylene Diene Monomer) found in sheets and rolls for gaskets by Planix™ is a family of synthetic rubbers classified under group M according to DIN/ISO 1629. Its unique composition provides resistance to heat, atmospheric agents, aging, and seawater, making it an ideal material for applications requiring high performance in adverse environmental conditions.

Characteristics

Planix™ EPDM rubbers stand out for their exceptional resistance to heat, atmospheric agents (UV rays), aging, and seawater. These features make them ideal for situations requiring significant ozone resistance and temperature variations. Seals made with EPDM are particularly recommended for contact with low-concentration acids and solvents.

Applications

Planix™ EPDM is recommended for a wide range of applications, thanks to its properties of thermal resistance, resistance to atmospheric and chemical agents. It is particularly suitable for seals in contact with low-concentration acids and solvents, offering reliable performance even in challenging environmental conditions.

Tech Data

Properties	Unit	Value
Colour	--	Black
Specific gravity	g/cm ³	1,25 +/- 0,05
Tensile strenght	MPa	6,5
Elongation at break	%	350
Tear resistance	MPa	17
Hardness	Deegres	65 +/- 5 SH
Compression Set (22 hrs at 70°C)	%	35
Temperature	°C	-40 to 120
Dimensions		
Width (+/- 5%)	mm	1000 to 1500, related to the thickness
Lenght (+/- 5%)	m	1 to 10, related to the thickness
Thichness (+/- 5%)	mm	1 to 50

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- Other gasketing sheet dimensions and thicknesses are available on request



Planix™ PX03 65SH

The range of sheets and rolls for gaskets by Planix™ offers a wide selection of materials, including various types of rubber, mica, thermal-insulating cardboard, and GRE. EPDM (Ethylene-Propylene Diene Monomer) is a family of synthetic rubbers classified under group M according to DIN/ISO 1629. Due to their resistance to heat, atmospheric agents (UV rays), aging, and seawater, EPDM rubbers are recommended where excellent ozone resistance and thermal excursions are required. They are particularly suitable for seals in contact with low-concentration acids and solvents.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.



Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it