

# PTFE JOINTING SHEET PLANIFLON™ B13

### Composition

- Modified PTFE resin
- Silica filler

#### **Characteristics**

The Planiflon™ range has been developed to operate from cryogenic temperatures up to 260°C and can be used with all the most aggressive fluids (ph 0-14). Planiflon™ B13 is a gasketing sheet that exhibits excellent chemical resistance, with moderate gas permeability. The creep properties are markedly better when compared to conventional PTFE. It can be used with strong acids (except hydrofluoric acid) and is suitable for applications with fuels, solvents, water, steam and chlorine.

## **Applications**

Planiflon™ B13 is suitable for industrial applications for sealing the flanges and has the following certificates:

- TA LUFT
- DVGW
- BAM
- FDA

#### Tech Data

Planiflon™ B13				
Colour			Fawn	
Filler			Silica	
Density		g/cm³	2.2	
Temperature		°C	-200/+260	
Max operating pressure		bar	83	
P x T max		bar x °C	-	
thickness 0,5 to 2,0			12000	
thickness 3,0			8600	
Compression range	DIN 3535-6	%	>4	
Creep	DIN 3535-6	%	<24	
Recovery	DIN 3535-6	%	>1.7	
Leakage	DIN 3535-6	mg*s-1*m-1	<0.05	
PH Range			0 ÷ 14	

- Never use the product at its maximum rated temperature and pressure. Consult the manufacturer for further information.
- The peak temperature can be sustained only for short exposure periods. Other gasketing sheet dimensions and thicknesses are available on request
- The dimensional tolerances of the gasketing sheets are: W and L  $\pm 3.0\%$ , H  $\pm 10.0\%$

Size	1.500 x 1.500 - (1000 x 1000 sp. 0.75 mm)	60" x 60" - (40" x 40" tk. 1/32")
Thickne	ss 0,75 ÷ 6,00 mm	1/32" ÷ 1/4"



## PTFE Jointing Sheet Planiflon™ B13

The bidirectional structured PTFE gasketing sheets Planiflon™ are made with special resins and inorganic fillers. The special processing technique minimizes the material's cold flow, giving to the sheets the characteristic attribute of bidirectionality. The product range of the Planiflon™ includes the following products:

- B13 Modified PTFE with silica filler
- B14 Modified PTFE with hollow glass microspheres filler
- B15 Modified PTFE with barium sulphate filler
- B58 Microcellular Modified PTFE layers with pure modified PTFE core
- **B60** Microcellular Modified PTFE with Inorganic fillers
- E12 Bi-directional expanded PTFF



