



# PTFE PACKING PL5000L

## Composition

Multifilament 100% PTFE yarn  
Silicone-free inert lubricant



## Characteristics

The PL5000L packing is a reliable solution for dynamic applications that require the use of PTFE. Made from pure PTFE multifilament yarn and formulated with a silicone-free lubricant additive, this packing exhibits great versatility as it can be used for many services where PTFE is required. It is important to remember that minimum/maximum temperatures and maximum pressures should not be associated. With these features, PL5000L is a dependable option to be used in all those applications that require high chemical resistance in almost the entire pH range.

## Applications

The PTFE packing PL5000L can be used with all acidic and basic fluids compatible with PTFE, for seals on reciprocating pumps, centrifuges, and moderate-speed agitators. Available in the PT5504AL superior version for food use and PT5500 OX for oxygen service, the PL5000L braid guarantees high performance and is suitable for a wide range of applications.

## Tech Data

	P bar	lbf/in2	Vm/S	f/pm	pH	T°C	T°F
	50	750	2	400	0 ÷ 14	-100 ÷ 280	-330 ÷ 540
	20	300	5	1000			

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures



## PTFE Packing PL5000L

The family of the PTFE articles include a wide range of braided packings that can cover all applications that require the use of this material. White PTFE yarn is commonly used in gland sealing systems, both in static and dynamic applications with moderate-speed, thanks to the properties of this material, which ensures efficient and reliable sealing that can cover almost the entire pH range. The packings are available in both dry and lubricated configuration, in combination with other fibers such as aramid or with a rubber core. Among the special products are those intended for use with food and for oxygen service.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

 **CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)



# PTFE PACKING PL5000L

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8	1	2.2	58.5	192	58.5	87.1
4	-	1	2.2	32.9	108	32.9	49
5	3/16	1	2.2	21.1	69	21.1	31.4
6	-	2.5	5.5	36.5	120	14.6	21.8
6.5	1/4	2.5	5.5	31.1	102	12.5	18.6
8	5/16	2.5	5.5	20.6	67	8.2	12.2
9.5	3/8	2.5	5.5	14.6	48	5.8	8.7
10	-	2.5	5.5	13.2	43	5.3	7.8
11	7/16	2.5	5.5	10.9	36	4.3	6.5
12	-	2.5	5.5	9.1	30	3.7	5.4
12.7	1/2	2.5	5.5	8.2	27	3.3	4.9
14	9/16	5	11	13.4	44	2.7	4
16	5/8	5	11	10.3	34	2.1	3.1
17.5	11/16	5	11	8.6	28	1.7	2.6
18	-	5	11	8.1	27	1.6	2.4
19	3/4	5	11	7.3	24	1.5	2.2
22	7/8	5	11	5.4	18	1.1	1.6
25.5	1	5	11	4.0	13	0.8	1.2

- The weight per meter and the packaging's weight may have a tolerance of +/- 10%. Other sizes and packaging are available on demand.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

**CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)