RING TYPE JOINT PLANISTEEL RTJ K

Composition

Available models of Planisteel RTJ K Ring Type Joint Gaskets:

- R in accordance with ASME B16.20 - API 6A
- Custom RTJ
- all featuring an integrated test port within the gasket body

Characteristics

This gasket is specifically designed for use with flanges featuring grooves, commonly known as RTJ flanges.

The main characteristics of the product are as follows:

- RTJ K incorporates a monitoring port that allows the gasket sealing performance to be tested or monitored by providing external access to the annular cavity between the gasket and the grooves.
- The special configuration of this gasket is designed to allow the primary and secondary sealing surfaces of the RTJ flange to be tested, either separately or simultaneously, to ensure proper sealing integrity.
- Service temperature and pressure, together with the gasket's corrosion resistance, depend on the selected metallic material.

Applications

The RTJ K gasket is installed in the flange groove like a conventional RTJ gasket, but the small test port (hole) incorporated into the gasket body provides access to the annular cavity between the groove and the RTJ. After the flanges have been correctly assembled and tightened, a gas or liquid can be introduced through this port to pressurize the space between the sealing surfaces, allowing the flange sealing integrity to be verified before the system is brought to full operating pressure. Once the specified test pressure has been reached, maintaining it within the limits established by the procedure provides an indication of sealing integrity, while any pressure drop may indicate a potential leakage path.

This method allows each joint to be tested individually without pressurizing the entire line. Since the test volume is very small, the test is quick and efficient and requires only a minimal amount of test fluid.
This approach enables early detection of potential leaks and significantly reduces the risk of failures during operation.
It also provides greater reliability for high-pressure RTJ connections and can be equipped with a monitoring line to verify sealing integrity over time.


Planisteel RTJ K is particularly suitable for high-pressure RTJ connections and critical services in the Oil & Gas, petrochemical, refining and process industries.



Ring Type Joint Planisteel RTJ K

Planisteel RTJ K is a special metallic Ring Type Joint (RTJ) gasket designed to allow verification of the integrity of the flanged connection after assembly and before the system is pressurized.

Planisteel RTJ K Ring Type Joint gaskets are available in all materials, from high-carbon materials to steels and all types of alloys. Carrara maintains a large stock for immediate availability **RTJ Stock List**.



The information provided in this publication, as well as that supplied to users in other forms, is based on our experience and communicated according to the best knowledge available. However, since numerous factors beyond our knowledge and control may influence the use of the products, no warranty, explicit or implicit, is given regarding such content. The operating limits indicated do not constitute confirmation that these values can be applied simultaneously. Avoid using the product at the maximum temperature and pressure limits. The maximum temperature is sustainable only for short periods under specific conditions. Specifications may be changed without notice. The images in the DS may not exactly represent the product, its color and/or marking.

GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 carrara.it - info@carrara.it