



VALVE PACKING CONTROLLER 2 EVO

Composition

- Rings: Flexible graphite VALVOGRAPH E coated with 5% PTFE
- Wiper rings: Compression packing GR80SGR coated with 5% PTFE
- Impregnated with pure colloidal graphite and a special compound

Characteristics

The Controller 2 Evolution PTFE boasts the following distinctive features:

- Approved for low-emission services in accordance with TA LUFT VDI2440 standards
- Equipped with the special GR80SGR packing coated in PTFE, offering excellent recovery combined with very high aging resistance
- Can easily operate with all industrial fluids in high-pressure and temperature services, according to EN 14772 - Section 6.7 weight loss requirements

Applications

This kit is specifically designed for low-emission and high-pressure/temperature services of industrial valves, providing reliable and durable performance in demanding environmental conditions.

Tech Data

P bar	lbf/in2	Vm/S	f/pm	pH	T °C	°F
500	7500	1	200	0+14	-100 ÷ 450	-150 ÷ 840

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information



Valve Packing Controller 2 Evo

The Controller 2 Evolution PTFE is an alternative version of our renowned stem packing kit for industrial valves, designed to ensure optimal performance in low-emission and high-pressure, high-temperature environments. Approved for low-emission services compliant with the stringent TA LUFT VDI2440 standards, this set is equipped with a special GR80SGR packing coated in PTFE, offering remarkable recovery capability and high aging resistance.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

CARRARA
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it