



# VALVE PACKING CONTROLLER-ONE EVO

## Composition

The Controller One Evo sealing ring kit consists of expanded mineral graphite Valvograph and GR80SGR braid. This set has been designed and manufactured to meet the growing demand for reliable products that comply with TA LUFT VDI 2440 Low Emission requirements. The graphite rings are stamped in the characteristic Cup & Cone section, which, when compressed, generates a thrust towards the stem and the chamber, improving the sealing level and meeting low emission requirements even with low clamping loads. Controller One Evolution is made with pure graphite to ensure moderate weight loss at high temperatures, in accordance with EN14772 - Section 6.7 requirements.


## Characteristics

This set of gaskets for industrial valves is designed for low emission applications with hydrocarbons, hydrogen, VOCs, VHAP, non-oxidizing chemicals, and steam. Its Cup & Cone configuration allows for maintaining a high seal even with reduced clamping loads. The pure graphite used offers superior resistance to high temperatures and operating loads, meeting the strictest requirements for industrial applications.

## Applications

Controller One Evolution is ideal as a stem sealing set for industrial valves in low emission applications. Thanks to its ability to maintain reliable sealing even in severe operating conditions and its chemical and thermal resistance properties, it is suitable for a wide range of industrial services, ensuring reliable performance and compliance with the highest safety and regulatory standards.

## Tech Data

	P bar	lbf/in2	Vm/S	f/pm	pH	T°C	T°F
	300	4500	1	200	0÷14	-200 ÷ 450 / 650	-325 ÷ 840 / 1200

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 °C
- With steam and non-oxidizing fluids the temperature must be limited to 650 °C
- Graphite and carbon cannot be used with oxidizing fluids



## Valve Packing Controller-One Evo

The range of graphite products for industrial valve stems offers a wide selection of models to ensure optimal choice in every situation. These gaskets are made from materials that meet rigorous industry standards, including ASTM F2168 and ASTM F2191, taking into account the main deviations provided for by IOGP standards and major oil and gas producers. The Carrara range ensures a level of certification suitable for every technical specification and sustainable application of graphite products.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

 **CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)