



VALVE PACKING PGT1 C8248

Composition

The kit includes sealing rings made of Valvograph expanded graphite paired with the C8200 braid, characterized by pre-oxidized carbon. This combination of high-quality materials ensures effective and long-lasting sealing even in challenging industrial conditions.



Characteristics

The PGT1 C8248 braid boasts a proven and reliable design, ensuring excellent stem sealing even in demanding industrial environments. Thanks to its heat and wear resistance, this braid offers consistent performance over time, minimizing leaks and ensuring efficient operation of industrial valves.

Applications

Ideal for medium-temperature industrial applications, the PGT1 C8248 braid is suitable for use with steam, gas, and a wide range of chemical and petroleum products. This sealing kit is the perfect choice for valves used in various industrial sectors, offering a reliable and cost-effective solution to ensure optimal sealing and consistent performance over time.

Tech Data

	bar	lb/in2	m/s	fpm	pH	T°C	T°F
	200	3000	1	200	2 ÷ 12	-100 ÷ 350 / 500	-150 ÷ 660 / 930
	150	2250	2	400	2 ÷ 12	-100 ÷ 350 / 500	-150 ÷ 660 / 930

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- Graphite and carbon cannot be used with oxidizing fluids



Valve Packing PGT1 C8248

The PGT1 C8248 braid is a high-quality stem sealing kit designed for medium-temperature industrial needs. Combining Valvograph expanded graphite sealing rings with the C8200 braid, it provides a reliable and cost-effective solution for a wide range of industrial applications.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

 **CARRARA**
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it