



WELD RING GASKETS

Characteristics

A **weld ring gasket**, commonly also known as a **lip seal weld ring gasket**, consists of a pair of metallic rings. Each ring is initially welded to the flange surface. During joint assembly, the two rings are then welded together along the outer edge, thus completing the seal.

Code	Description
WG-M 	Basic solution for applications where the space between flanges is limited. Widely used according to DIN 2695, rings with 4 mm thickness (*).
<i>Typical thickness: 4 mm - Re-weld times: up to 5 - Radial compensation: 0.3 mm</i>	
WG-R1 	Similar to type WG-M, but with the possibility of both external and internal weld beads, which greatly facilitate installation (*).
<i>Typical thickness: 15 mm - Re-weld times: up to 5 - Radial compensation: 0.1 mm</i>	
WG-R4 	Advanced sealing solution with hollow-lip welded ring, especially recommended for large diameter joints. Offers greater resistance to thermal and pressure shocks compared to WG-M and WG-R1 models. Capable of compensating high axial and radial differential expansions; extremely resistant to thermal and pressure shocks.
<i>Typical thickness: 20 mm - Re-weld times: from 2 to 4 - Radial compensation: 5 mm</i>	

(*) In compliance with DIN 2695:2002 for DIN flanges.

All welded rings can be manufactured according to customer drawings.


Applications

These weld ring gaskets represent a permanent metallic sealing solution, used in applications where sealing reliability is essential and the need for joint disassembly is limited.

The welds associated with this type of gasket are sealing welds and not structural, since their function is exclusively to ensure the continuity of the sealing barrier, not to contribute to the mechanical strength of the connection.

Tech Data

Sealing Factors	S_g	S_{gmin}	S_{g0min}	S_{gmax}
Mpa	70	35	15	400



Weld Ring Gaskets

Possible configurations:

- **Membrane gaskets**
(membrane weld ring gaskets)
- **Profiled gaskets**
(profiled weld ring gaskets)
- **Hollow-lip gaskets**
(hollow-lip weld ring gaskets)

The use of **lip seal weld ring** gaskets is recommended when conventional gaskets are unsuitable and when joint disassembly is infrequent.

These gaskets are generally classified as **semi-removable**, since opening the joint requires cutting the sealing weld in addition to removing the flange bolts.



The information provided in this publication, as well as that supplied to users in other forms, is based on our experience and communicated according to the best knowledge available. However, since numerous factors beyond our knowledge and control may influence the use of the products, no warranty, explicit or implicit, is given regarding such content. The operating limits indicated do not constitute confirmation that these values can be applied simultaneously. Avoid using the product at the maximum temperature and pressure limits. The maximum temperature is sustainable only for short periods under specific conditions. Specifications may be changed without notice. The images in the DS may not exactly represent the product, its color and/or marking.



Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 carrara.it - info@carrara.it