



CONTROLLER 3 EVO

Composition

Reinforced graphite packing made with preformed rings of **GR80SGR** type flexible graphite braided gland packing

Characteristics


The **CONTROLLER 3 EVO** expanded graphite is a packing for industrial valves. The GR80SGR packing ensures high performance in operation across the full temperature range, while offering a low coefficient of friction.

CONTROLLER 3 EVO, certified for **Low Emission according to ISO 15848 BH-C01**, maintains its elasticity and sealing properties over time, ensuring safe valve operation.

Applications

CONTROLLER 3 EVO is specifically designed for industrial valves in Low Emission services according to ISO 15848 BH-C01. It is also suitable for HP/HT steam services and hydrogen applications.

Tech Data

	P bar	lbf/in ²	Vm/S	f/pm	pH	T°C	T°F
	500	7500	1		0 ÷ 14	-200 ÷ 450 / 650	-330 ÷ 850 / 1200

- Never use the product at its maximum rated temperature and pressure. Consult the manufacturer for further information.
- The peak temperature can be sustained only for short exposure periods.
- With weakly oxidizing agents and hot air, the temperature must be limited to 450 °C.
- With steam and non-oxidizing fluids, the temperature must be limited to 650 °C.
- Flexible graphite and carbon yarns shall not be used with oxidizing fluids.



CONTROLLER 3 EVO

Graphite stem sealing packing for industrial valves, made with expanded graphite sealing rings for Low Emissions services, approved according to ISO 15848 BH-C01.



The information provided in this publication, as well as that supplied to users in other forms, is based on our experience and communicated according to the best knowledge available. However, since numerous factors beyond our knowledge and control may influence the use of the products, no warranty, explicit or implicit, is given regarding such content. The operating limits indicated do not constitute confirmation that these values can be applied simultaneously. Avoid using the product at the maximum temperature and pressure limits. The maximum temperature is sustainable only for short periods under specific conditions. Specifications may be changed without notice. The images in the DS may not accurately represent the product's color and/or marking.



Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 www.carrara.it - info@carrara.it