

CONTROLLER 3 EVO OXYGEN BAM

Composition

The **CONTROLLER 3 EVO OXYGEN BAM** is comprised of **GR80SGR OXY** braided rings, consisting of expanded graphite wires with a dedicated metal reinforcement. This material ensures minimal weight loss even in the most extreme conditions, meeting the stringent requirements of **EN14772** - section 6.7. BAM approved No. 2-28/2015 E for use with both liquid and gaseous oxygen.

Characteristics

The **CONTROLLER 3 EVO OXYGEN BAM** offers a unique combination of strength and durability, with a low friction coefficient ensuring smooth and reliable operation. Its reinforced structure and the quality of the graphite used make it ideal for high-temperature and pressure applications.

Applications

Specifically designed for industrial valves in oxygen service, the **CONTROLLER 3 EVO OXYGEN BAM** is the ideal choice to ensure effective stem sealing in critical environments. It provides superior performance and exceptional durability, making it essential for oxygen-sensitive industrial applications.

Tech Data

Maximum Temperature °C	Maximum Oxygen Pressure bar
up to 60	350
>60 up to 300	220

Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information



CONTROLLER 3 EVO OXYGEN BAM

The CONTROLLER 3 EVO OXYGEN BAM is an innovative gland packing designed specifically for industrial

designed specifically for industrial valves in oxygen service. Made from high-quality expanded mineral graphite and reinforced with special metal, this product offers reliable and safe performance in oxygen environments.





