



PGT3 GR8622

Composition

API std 622 3rd Edition packing approved.

PGT3 GR8622 it's a special 5 formed rings sealing flexible graphite packing. The yarns guarantee a very low weight loss (according to EN 14772, section 6.7) and great sliding properties. PGT3 GR8622 guarantees for long time great recovery and do not need retightening.

Characteristics

Full braided packing kit of pure flexible graphite strands knitted wire, impregnated with colloidal graphite and special compounds

Applications

PGT3 GR8622 is specific for Industrial Valves Low Emission service, suitable also for HP/HT applications.

Tech Data

P bar	lbf/in2	Vm/S	f/pm	pH	T °C	T °F
500	7500	2	400	0+14(3)	-200 ÷ 450(1) / 650(2)	-328 ÷ 840(1) / 1200(2)



PGT3 GR8622

API std 622 3rd Edition packing approved for Industrial Valves Low Emission services



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.



Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it