



PLANIGRAPH V48EC8200

Composition

- V48E : Die-formed flexible graphite high carbon content C > 99%
- C8200: Top&Bottom wiper braided packing rings style C8200 preoxidized PAN carbon yarns



Characteristics

Planigraph V48EC8200 graphite gasket offers reliable and long-lasting sealing in medium-temperature environments. The combination of high-quality graphite and C8200 yarn ensures optimal performance in industrial applications.

Applications

This graphite gasket in sealing set is ideal for valves used in medium-temperature environments. It can be used to ensure sealing with steam, gas, and most chemicals and petroleum products. However, use with strong oxidizers should be avoided.

Tech Data

P bar	lbf/in ²	Vm/S	f/pm	pH	T°C	T°F
	200	3000	1	200	0 ÷ 14	-100 ÷ 350 / 500

- The peak temperature can be sustained only for short exposure periods.
- With weakly oxidizing agents and hot air, the temperature must be limited to 450 °C.
- Flexible graphite and carbon yarns shall not be used with oxidizing fluids.
- With weakly oxidizing agents and hot air, the temperature must be limited to 350°C.

Planigraph V48EC8200

Planigraph V48EC8200 is a graphite gasket in sealing set designed to ensure optimal performance in medium-temperature industrial environments. ALSO AVAILABLE WITH REINFORCED WIPER STYLE C8300/R



The information provided in this publication, as well as that supplied to users in other forms, is based on our experience and communicated according to the best knowledge available. However, since numerous factors beyond our knowledge and control may influence the use of the products, no warranty, explicit or implicit, is given regarding such content. The operating limits indicated do not constitute confirmation that these values can be applied simultaneously. Avoid using the product at the maximum temperature and pressure limits. The maximum temperature is sustainable only for short periods under specific conditions. Specifications may be changed without notice. The images in the DS may not accurately represent the product's color and/or marking.



GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,

Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 www.carrara.it - info@carrara.it