



# PLANIGRAPH V48EC8200

## Composition

- V48E : Die-formed flexible graphite high carbon content C > 99%
- C8200: Top&Bottom wiper braided packing rings style C8200 preoxidized PAN carbon yarns


## Characteristics

PLANIGRAPH V48EC8200 offers reliable and long-lasting sealing in medium-temperature environments. The combination of high-quality graphite and C8200 yarn ensures optimal performance in industrial applications.

## Applications

This sealing set is ideal for valves used in medium-temperature environments. It can be used to ensure sealing with steam, gas, and most chemicals and petroleum products. However, use with strong oxidizers should be avoided.

## Tech Data

	P bar	lbf/in <sup>2</sup>	Vm/S	f/pm	pH	T °C	T °F
	200	3000	1	200	0 ÷ 14	-100 ÷ 350 / 500	-150 ÷ 660 / 930

- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 °C
- Graphite and carbon cannot be used with oxidizing fluids
- With weakly oxidizing agents and hot air the temperature must be limited to 350 °C



## PLANIGRAPH V48EC8200

PLANIGRAPH V48EC8200 is a sealing set designed to ensure optimal performance in medium-temperature industrial environments.

ALSO AVAILABLE WITH REINFORCED WIPER STYLE C8300/R



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

**CARRARA**  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)