



# PRESSURE SEAL GASKET G44

## Composition

- Expanded graphite with C>99% purity
- Metallic covers
- SS316 inserts


## Characteristics

The Pressure Seal Steelgraph G44 gasket features a combination of expanded graphite reinforced with steel sheets and metallic covers. This design offers optimal protection against extrusion while maintaining high elasticity and resistance. The gasket can withstand high pressures and ensures reliable sealing even in extreme operating conditions.

## Applications

This type of gasket is specifically designed for pressure seal valve systems. It is ideal for high-pressure applications where reliable and durable sealing is required.

## Tech Data

	P bar	lbf/in <sup>2</sup>	Vm/S	f/pm	pH	T °C	T °F
	1500	22500			0÷14	-200 ÷ 450 / 650	-330 ÷ 840 / 1200

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 ° C
- With steam and non-oxidizing fluids the temperature must be limited to 650 ° C



## Pressure Seal Gasket G44

The Pressure Seal Steelgraph G44 gasket is designed for high-pressure valves, manufactured by molding expanded graphite reinforced with steel sheets and assembled with two SS 316 covers (or other steel upon request). This configuration provides effective protection against extrusion while ensuring excellent elasticity and resistance properties.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.



**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)