



VALVE PACKING CONTROLLER-ONE Z

Composition

- **V48Z:** Pure nuclear-grade graphite VALVOGRAPH
- **GR 8807 INCOBRAID®:** Graphite P.A.N. reinforced with discontinuous NiCr microfilament, impregnated with pure graphite, inorganic corrosion inhibitor, and zinc

Characteristics

Controller-One EVO Z is entirely made of graphite, ensuring excellent chemical and thermal resistance. The special structure, with the presence of Incobraid® GR8807 as Top and Bottom, offers exceptional extrusion resistance, allowing for greater sealing with a lower clamping load. This makes it particularly suitable for applications with steam, gas, and most chemicals and petroleum products. However, use with strong oxidizers should be avoided.

Applications

Specifically designed for valves, Controller-One EVO Z is suitable for ensuring sealing in a wide range of industrial services, including those with steam, gas, and chemicals. Its extrusion resistance and ability to maintain sealing even with a lower clamping load make it a reliable choice for industrial applications.

Tech Data

P bar	lbf/in2	Vm/S	f/pm	pH	T °C	°F
300	4500	1	200	0÷14	-100 ÷ 450 / 650	-150 ÷ 840 / 1200

- The peak temperature can be sustained for short exposures
- With weakly oxidizing agents and hot air the temperature must be limited to 450 °C
- Graphite and carbon cannot be used with oxidizing fluids
- Do not use the product at maximum temperature values or under pressures higher than those typical of flue gases. Consult the manufacturer for further information.



Valve Packing Controller-One Z

The set of expanded graphite rings with trapezoidal section (Valvograph V48Z) with head and bottom in GR8807 INCOBRAID® graphite braid represents a reliable solution to ensure sealing in a wide range of industrial applications.



The information in this publication, as well as any additional information provided to users, is based on experience and is shared to the best of our current knowledge. However, due to numerous factors beyond our knowledge and control that may affect the use of these products, no warranties are provided or implied regarding this information. The operating limits presented in this publication do not imply that these values can be applied simultaneously. Do not use the product at the maximum temperature and pressure values simultaneously. The maximum temperature is suitable only for short-term exposure under specific conditions. Specifications are subject to change without prior notice. The picture in the DS may not accurately depict the exact color and/or markings of the product.

CARRARA®
GLOBAL SEALING SOLUTIONS

Carrara S.p.A.,
Via Provinciale 1/E - 25030 Adro - BS - Italia
tel. +39 030 7451121 / fax +39 030 7451130
www.carrara.it - info@carrara.it