



# VALVE PACKING PGT1 C8248

## Composition

The kit includes sealing rings made of Valvograph expanded graphite paired with the C8200 braid, characterized by pre-oxidized carbon. This combination of high-quality materials ensures effective and long-lasting sealing even in challenging industrial conditions.



## Characteristics

The PGT1 C8248 braid boasts a proven and reliable design, ensuring excellent stem sealing even in demanding industrial environments. Thanks to its heat and wear resistance, this braid offers consistent performance over time, minimizing leaks and ensuring efficient operation of industrial valves.

## Applications

Ideal for medium-temperature industrial applications, the PGT1 C8248 braid is suitable for use with steam, gas, and a wide range of chemical and petroleum products. This sealing kit is the perfect choice for valves used in various industrial sectors, offering a reliable and cost-effective solution to ensure optimal sealing and consistent performance over time.

## Tech Data

	bar	lb/in <sup>2</sup>	m/s	fpm	pH	T°C	T°F
	200	3000	1	200	2 ÷ 12	-100 ÷ 350 / 500	-150 ÷ 660 / 930
	150	2250	2	400	2 ÷ 12	-100 ÷ 350 / 500	-150 ÷ 660 / 930

- Never use the product to the maximum temperature and pressure associated. Consult the manufacturer for further information
- Graphite and carbon cannot be used with oxidizing fluids



## Valve Packing PGT1 C8248

The PGT1 C8248 braid is a high-quality stem sealing kit designed for medium-temperature industrial needs. Combining Valvograph expanded graphite sealing rings with the C8200 braid, it provides a reliable and cost-effective solution for a wide range of industrial applications.



The information in this publication and otherwise provided to users is based on experience and is provided to the best of our current knowledge. Due to many factors which are beyond our knowledge and control affecting the use of the products, no warranties are given or are to be held implied with respect to such information. The operating limits shown in this publication do not constitute a statement that these values can be applied simultaneously. Do not use the product at the associated maximum temperature and pressure values. The maximum temperature can be sustained for short exposures in particular conditions. Specifications are subject to change without notice.

  
GLOBAL SEALING SOLUTIONS

**Carrara S.p.A.**,  
Via Provinciale 1/E - 25030 Adro - BS - Italia  
tel. +39 030 7451121 / fax +39 030 7451130  
[www.carrara.it](http://www.carrara.it) - [info@carrara.it](mailto:info@carrara.it)