



STEELGRAPH G33



T	°C	-100	+450 (1) / +650 (2)
P	bar	1500	
pH		0 ÷ 14(3)	

(1) Con agenti ossidanti / *With mild oxidizers*

(2) Applicazioni vapore / *With steam*

(3) Non utilizzare con prodotti fortemente ossidanti / *Avoid the strong oxidizers*

(4) Non utilizzare il prodotto ai valori massimi di temperatura e pressione associati senza prima consultare il produttore / *Avoid the product's use at the maximum temperature and pressure values associated without consult the manufacturer*

PRESSURE SEAL GASKET

Materiali

- Grafite espansa
- Anelli anti-estrusione

Caratteristiche

Steelgraph G33 è una guarnizione ottenuta per stampaggio di grafite espansa con inserimento di anelli metallici sui corners.

Questa soluzione permette di coniugare l'elevata elasticità della grafite con una eccellente resistenza alla estrusione.

Applicazioni

Guarnizione per Pressure Seal Valve e portelloni dei condensatori di alta e media pressione di centrali termoelettriche.

Materials

- Flexible graphite
- Anti-extrusion rings

Features

Steelgraph G33 is a die-formed graphite gaskets reinforced on the corners with metallic rings.

This solution allows to protect the gaskets from the extrusion, offering great recovery and resistance.

Applications

Pressure Seal Valve's Gasket, suitable also for condenser's door in Power Plants.