




TECHNICAL DATA SHEET - CST 0090/02 - 04/10/2016

V9907

(*)				
T	°C	-50 / 500		
p	bar	200		20
V	m/s	1.5		5
pH		2 ÷ 12		



(*) Do not use the product to the maximum temperature and pressure associated without consult the manufacturer; with steam the temperature has to be limited to 350°C.

Composition

- E glass fiber
- Graphite/PTFE impregnation
- Corrosion inhibitor
- Lubricant silicon free

Features

Make by glass yarns (where the fibres 6-micron length are increased to 9 micron through a special process and twisted) impregnated with a special compound based on high content of graphite and corrosion inhibitor.

Applications

Suitable for general applications, on the valves or as manhole's gasket. Do not use glass material with stream which the experiences shown limited compatibility.

Size mm	Size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	74,1	243	74,1	110,3
4,0	-	1,0	2,2	41,7	137	41,7	62,1
5,0	3/16	1,0	2,2	26,7	87	26,7	39,7
6,0	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8,0	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10,0	-	2,5	5,5	16,7	55	6,7	9,9
11,0	7/16	2,5	5,5	13,8	45	5,5	8,2
12,0	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14,0	9/16	5,0	11,0	17,0	56	3,4	5,1
16,0	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18,0	-	5,0	11,0	10,3	34	2,1	3,1
19,0	3/4	5,0	11,0	9,2	30	1,8	2,8
22,0	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5

packaged +/- 10 % in weight