




TECHNICAL DATA SHEET - CST 0210/02 - 23/07/2014

PT 5600K

(*)				
T	°C	-200 +280		
p	bar	500	300	25
V	m/s	1.5	2	10
pH		3 + 12		

(*)Do not use the product to the maximum temperature and pressure associated without consulting the manufacturer

Composition

- Pure PTFE yarns by GORE
- Aramid yarns

Features

Packing braided with PTFE yarns in the core and Aramid yarn on the corners to improve the resistance.

Applications

Packing for reciprocating and centrifugal pumps, mixers and valves, suitable for acids, solvents, abrasive substances in paper mills, in the food and chemicals industries.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	65,4	214	65,4	97,4
4,0	-	1,0	2,2	36,8	121	36,8	54,8
5,0	3/16	1,0	2,2	23,5	77	23,5	35,0
6,0	-	2,5	5,5	40,8	134	16,3	24,3
6,5	1/4	2,5	5,5	34,8	114	13,9	20,7
8,0	5/16	2,5	5,5	23,0	75	9,2	13,7
9,5	3/8	2,5	5,5	16,3	53	6,5	9,7
10,0	-	2,5	5,5	14,7	48	5,9	8,8
11,0	7/16	2,5	5,5	12,2	40	4,9	7,2
12,0	-	2,5	5,5	10,2	34	4,1	6,1
12,7	1/2	2,5	5,5	9,1	30	3,6	5,4
14,0	9/16	5,0	11,0	15,0	49	3,0	4,5
16,0	5/8	5,0	11,0	11,5	38	2,3	3,4
17,5	11/16	5,0	11,0	9,6	32	1,9	2,9
18,0	-	5,0	11,0	9,1	30	1,8	2,7
19,0	3/4	5,0	11,0	8,1	27	1,6	2,4
22,0	7/8	5,0	11,0	6,1	20	1,2	1,8
25,5	1	5,0	11,0	4,5	15	0,9	1,3

Packaging +/- 10 % in weight; Customized sizes and packaging are available on demand